

Two Door Freezer, Lit Sign

Range: ActiveCore Freezer

SKOPE ID: LT13BYN

Dimensions: 1480 mm (W) × 745 mm (D) × 2210 mm (H)

Capacity: 1202 L

Project: _____

Item #: _____



A high-efficiency, top-mounted heavy duty display freezer suitable for both front and back of house applications. By using natural refrigerants the freezer achieves high performance with low energy consumption. This model has glass doors, with triple-glazed heated insulated panels with Active Condensation Control (heat is applied only when condensating), a lit sign and internal lighting, with customisable additional shelving, different locks, or specialised ICE storage. With L1 compliance it is engineered to serve frozen food at a standard -18°C to -21°C and is adjustable from -12°C to -26°C. It is certified under GEMS to the mandatory climate class 3 and is fully tested to operate in ambient environments of up to 40°C (climate class 5). The refrigeration cartridge can be fully removed in line with best practice for safe servicing of flammable refrigerants. The cabinet includes a controller that connects to the free SKOPE-connect app to enable you to set temperatures and alerts, monitor temperatures and energy, and more. The freezer is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty



ActiveCore Technology




Natural Refrigerant



GEMS



SKOPE-connect



Cabinet

Type	SKFT Freezer
Finish	Stainless steel or powdercoated galvanised steel with optional colours from within the available SKOPE range
Insulation	Type PU foam Thickness (mm) 50 Blowing Agent Cyclo-iso pentane (C5H10/C5H12)
Doors	Type Glass swing door (triple-glazed, heated, argon-filled) Height (mm) 1570 Opening Size Width (mm) 610
Shelving	Ten adjustable height plastic-coated wire shelves 10 × half width shelf (677W × 467D)
Lighting	Sign 1 × 20 W, 1400 mm LED strip Interior* 2 × 20 W, 1400 mm LED strip side light

Dimensions†

	External	Internal	Packed
Width (mm)	1480	1380	TBC
Depth (mm)	745	555	TBC
Height (mm)	2210 (castors)	1570	TBC
Weight (kg)	TBC	TBC	TBC
Capacity (L)	1202		
Footprint (m ²)	0.84		

Ventilation (mm)

Top	Sides	Rear
300	Not required	10

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet		Multiple cabinets	
	At each joint	At each end wall	At each joint	At each end wall
Less than 1 metre	±5 mm	±5 mm	±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm	-5 mm to +10 mm	-5 mm to +10 mm	+15 mm

Performance

Product Temperature Range (°C)	-18 to -21 (adjustable* from -12 to -26)	
Maximum Ambient Temperature (°C)	40	
Sound Level (dB(A))	Standard	65.1
	Hush Mode*	64.1

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	3
Product Temperature Class	L1 (less than -18°C)
Total Energy Consumption	22.40 kWh/24 h
Annual Running Costs	\$2453 (@ \$0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	2.3 m power cord with 3-pin, 10 amp plug
Current draw (A)	7.5

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)		
System Type	Removable cartridge		
Cartridge Weight (kg)	57.5		
Refrigerant/Charge	R290/136 g		
Nominal Capacity (W)	1097		
Heat Rejection (W)	Average	930	Peak 1070
Defrost Type	Hot gas		
Drainage	No plumbing required		

* Accessible via the free SKOPE-connect™ app.



SKFT1300N-AC
on the SKOPE website