


Description		Commercial refrigerator		
Model Number		BR-1271HP (AUH)		
Dimensions	Overall Dimension (W X D X H)	1200mm	750+(40) mm	850mm
	Outside Dimension (W X D X H)	794mm	587mm	573mm
Effective Volume		280 L		
Material	Overall Material	Stainless Steel Plate OUT:TTS443M-NO. 4		
	Door	Stainless Steel Plate OUT:TTS443M-NO. 4		
	Inner Material	Stainless Steel Plate IN: JYH21CT-2B		
	Net Rack	P.E. and painted steel wire footings		
	Insulation	Cyclopentane Horniness Froth		
Performance	Condition	External Temperature 30°C With no load not exposed to direct sunlight		
	Internal Temperature	Below 3 °C		
Temperature Setting Range		-2 ~ 10 °C		
Freezing Assembly	Compressor	Obturation Completed		
	Condenser	Fin Type Forced Circulation Of Cold Air		
	Evaporator	Fin Type Forced Circulation		
	Refrigerant	R290		
	Fan Motors	Evaporator	Single Phase INPUT DC 12V 6W	
		Condenser	Single Phase INPUT DC 12V 8.4W	
	Tem. Meter	Mini Computer Controlled		
Defrost	Mini Computer controlled ,Auto heat defrost			
Power Specification	Power	Single-Phase 220-240V 50HZ		
	Efficiency Consumption	Defrosting 247W		
		Cooling 260W		
Power		Power Cord Lenth: 3.0m		
Applicable Socket		2-plug with gronging end 10A 250V		
Table Foot		Colophony Control Bound 130mm		
Accessories		2 Net rack, 5 net rack support.		
Others		Condenser Filternet , figurethermometer		
Weight		94 kg		

Note:1. For the output power: The electromotor normal stipulatlated output power.



2. Please use this numerical value, if you want to express the electrical expender .

Panasonic Appliances Cold Chain (Dalian) Co.,Ltd

APPROVALS
Li Fei
2022.02.21

DESIGN
Lan Shaojuan
2022/02.21

SCALE
A 4
1 / 3 0

SUR-1271HP (AUH) -00
DATE 2022.02.21

PART CODE
PRODUCT NAME

BR-1271HP(AUH)