








\*Customized
Caster H=115mm
Power Cord Australian 3 Pin Plug
ML Door











ITEM	Hoshizaki Undercounter Freezer				
MODEL	FTE-170SDA-GN-ML				
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity:0.95kVA(4.1A)				
AMPERAGE	Rated 3.4A Starting 14.8A				
ELECTRIC CONSUMPTION	Motor 510W(Power Factor69%) Heater 398W Refrigeration 578W Defrost 398W				
HEAT REJECTION	***W				
POWER CORD	2.5m (Plug with Earth Wire)				
EFFECTIVE CAPACITY	412L				
OUTSIDE DIMENSIONS	W1660×D700×H815mm				
INSIDE DIMENSIONS	W1290×D527×H588mm				
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom				
INTERIOR	Stainless Steel, ABS Plastic				
INSULATION	Polyurethane Foam				
REFRIGERATION SYSTEM	Forced Air Circulation				
DEFROST SYSTEM	Glass Tube Heater				
COMPRESSOR	Hermetic 385W				
CONDENSER	Fin and Tube type, Air—cooled				
EVAPORATOR	Fin and Tube Type				
REFRIGERANT	R404A				
TEMPERATURE CONTROL	Microprocessor controlled Adjustable from −25 to −70				
DEFROST CONTROL	Microprocessor controlled				
ELECTRIC CIRCUIT PROTECTION	10A Fuse, Earth Wire				
COMPRESSOR PROTECTION	Motor Protector				
LEG	Urethane (76mm DIA 115mm HIGH)				
WEIGHT	Net:109kg (Gross: Approx. **kg)				
PACKAGE	Carton (Wooden Pallet) 1735mm(W) x 780mm(D) x 990mm(H)				
ACCESSORIES	Shelf x 6, Shelf Clip x 20, Shelf Support x 2				
OPERATING CONDITIONS	Ambient Temperature:5-43° Voltage Range:Rated Voltage±6%				
*We reserve the right to make changes in specifications and design without prior notice					

- \*We reserve the right to make changes in specifications and design without prior notice.

  1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided.

  Allow 10mm extra space at the installation site to meet any installation requirements(additional spacing is also required for proper air flow).

  2. The heat rejection is based on the reached
- 2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 43°C and power supply of 23°OV 50°Hz. The amperage and electric consumption are based on measurements at ambient temperature of 43°C and power supply of 23°OV 50°Hz.
- 3. The cabinet temperature range of −25 to −7°c is guaranteed at ambient temperature of 30°c.
- 4. Product Code: T042-D009

*	*	Α	****	DATE	DRAWING NO.	SYMBOL
APPROVED	DESIGNED	SYMBOL	DATE	2018.02.09	1 021972	I /─\