



<https://www.commercialfridgefreezer.com.au/irinox-multifresh-next-m-standard/>

# Irinox MultiFresh Next M Standard Cold Storage Cabinet

**\$23,634.34** +GST

[View more Product Details](#)

[Add to Cart](#)

[Request a Quote](#)



IRINOX-MF-NEXT-M works on a standard performance level that can yield 50kg on a rapid freezing cycle. A temperature range of 90 to -18 degrees centigrade, an ambient temperature of 32 degrees centigrade, tray capacities of 18(GN1/1 or 600x400), 12(GN1/1 or 600x400), 9(GN1/1 or 600x400), energy consumption of 1.85kWh, and uses R290 gas. Also has 2 available configurations: Essential and Excellence.

## Description

Irinox MultiFresh Next M Standard Cold Storage Cabinet

### Features include:

- Door opening on the left with hinges on the left
- Patented concealed hinges

<https://www.commercialfridgefreezer.com.au/irinox-multifresh-next-m-standard/>

- Full height door with double bevelled side edges
- Door opening up to 160°
- Magnetic and slow closing of the door
- Equipped with 10-chamber gasket designed for high and low temperatures
- Core probe with 3 detection points
- Anti-corrosion
- Watertight IP67
- Large magnetic flat surface (400x150 mm)
- Easy removal and cleaning of the condenser filter
- Ergonomic and robust handle made of steel
- Stainless steel internal and external
- Built-in air condensation
- R290 refrigerant gas
- Patented adjustable tray holder
- 10 pairs of guides included
- WIFI module included for the HACCP report download

## Additional Information

Country of Manufacture	Italy
External Colour	Stainless Steel
Brand	Irinox
Model	MultiFresh Next M Essential
Warranty	24 Months
Temperature Operating Range C	90°C to -18°C
Temperature Display / Control	Yes
Climate / Ambient Temperature Rating	Ambient Rating C = 30°C
Refrigerant	R290
External Dimensions (mm)	790mm (W) x 1015mm (D) x 1590mm (H)
Other Details	Reach-In
Power Information	Power supply = 380-415V-3N 50Hz
Power Usage	Power usage kWh/24hr/m <sup>2</sup> = 44.4
Door Information	Door hinged = Left
Internal Colour	Stainless Steel
Tray Capacity & Height	18 Trays (GN1/1 or 600x400) (20 mm high) 12 Trays (GN1/1 or 600x400) (40 mm high) 9 Trays (GN1/1 or 600x400) (65 mm high)
Clear Ventilation Space Required	75mm back and sides
HACCP Memory & Alarm	Yes
Data Download Capability	WIFI module included for the HACCP report download
Gastronorm	Yes
About the Product	IRINOX-MF-NEXT-M is a propane blast chiller, ecological and completely customizable according to the needs of each professional choosing functions, type of performance, size of the display and the most useful features for its use.
Manufacturer's Suggested Retail Price	\$32,305.00