



<https://www.commercialfridgefreezer.com.au/irinox-multifresh-next-m-turbo/>

Irinox MultiFresh Next M Turbo Cold Storage Cabinet



IRINOX-MF-NEXT-M-TURBO owns a boosted yield of 65kg on quick freezing cycle, temperature span of 90 to -18 degrees centigrade, ambient rating of 40 degrees, power absorption of 5.4kW, also works on R290 gas, adaptable interface, HACCP data backup, variations of tray capacities: 9(GN1/1 or 600x400), 12(GN1/1 or 600x400), 18GN1/1 or 600x400).

Description

Irinox MultiFresh Next M Turbo Cold Storage Cabinet

Features include:

- Door opening on the left with hinges on the left
- Patented concealed hinges
- Full height door with double bevelled side edges
- Door opening up to 160°
- Magnetic and slow closing of the door
- Equipped with 10-chamber gasket designed for high and low temperatures

<https://www.commercialfridgefreezer.com.au/irinox-multifresh-next-m-turbo/>

Commercial Fridge and Freezer Sales Australia. All product images are provided for illustration purposes only. All specifications are subject to manufacturer changes without notice, so please check on the manufacturer's website for current product data.

- Core probe with 3 detection points
- Anti-corrosion
- Watertight IP67
- Large magnetic flat surface (400x150 mm)
- Easy removal and cleaning of the condenser filter
- Ergonomic and robust handle made of steel
- Stainless steel internal and external
- Built-in air condensation
- R290 refrigerant gas
- Patented adjustable tray holder
- 10 pairs of guides included
- WIFI module included for the HACCP report download

Additional Information

Country of Manufacture	Italy
External Colour	Stainless Steel
Brand	Irinox
Model	MF-NEXT-M-TURBO
Warranty	24 Months
Temperature Operating Range C	90Â°C to -18Â°C
Temperature Display / Control	Yes
Climate / Ambient Temperature Rating	Ambient Rating C = 40Â°C
Refrigerant	R290
External Dimensions (mm)	790mm (W) x 1015mm (D) x 1590mm (H)
Other Details	Reach-In
Power Information	Power supply = 380-415V-3N 50Hz
Power Usage	Power usage KWh/24hr/mÂ² = 129
Door Information	Door hinged = Left
Internal Colour	Stainless Steel
Tray Capacity & Height	18 Trays (GN1/1 or 600x400) (20 mm high) 12 Trays (GN1/1 or 600x400) (40 mm high) 9 Trays (GN1/1 or 600x400) (65 mm high)
Clear Ventilation Space Required	75mm back and sides
HACCP Memory & Alarm	Yes
Data Download Capability	WIFI module included for the HACCP report download
Gastronorm	Yes
About the Product	IRINOX-MF-NEXT-M-TURBO is a propane blast chiller, ecological and completely customizable according to the needs of each professional choosing functions, type of performance, size of the display and the most useful features for its use.
Manufacturer's Suggested Retail Price	\$0.00