



<https://www.commercialfridgefreezer.com.au/irinox-multifresh-next-s-turbo/>

Irinox MultiFresh Next S Turbo Cold Storage Cabinet



IRINOX-MF-NEXT-S-TURBO has a increase of yield of 32.5kg in its performance, it also has essential and excellence configurations, 90 to -18 centigrade temperature scale, climate class of 5, energy consumption of 1.6kW, runs on R290 gas, data connectivity that has data back up for HACCP, and variety of tray capacities such as 8(GN1/1 or 600x400), 5(GN1/1 or 600x400), 4(GN1/1 or 600x400).

Description

Irinox MultiFresh Next S Turbo Cold Storage Cabinet

Features include:

- Door opening on the left with hinges on the left
- Patented concealed hinges
- Full height door with double bevelled side edges
- Door opening up to 160°
- Magnetic and slow closing of the door

<https://www.commercialfridgefreezer.com.au/irinox-multifresh-next-s-turbo/>

- Equipped with 10-chamber gasket designed for high and low temperatures
- Core probe with 3 detection points
- Anti-corrosion
- Watertight IP67
- Large magnetic flat surface (400x150 mm)
- Easy removal and cleaning of the condenser filter
- Ergonomic and robust handle made of steel
- Stainless steel internal and external
- Built-in air condensation
- R290 refrigerant gas
- Patented adjustable tray holder
- 5 pairs of guides included
- 4 adjustable feet H 80-115 mm
- WIFI module included for the HACCP report download

Additional Information

Country of Manufacture	Italy
External Colour	Stainless Steel
Brand	Irinox
Model	MF-NEXT-S-TURBO
Warranty	24 Months
Temperature Operating Range C	90Â°C to -18Â°C
Temperature Display / Control	Yes
Climate / Ambient Temperature Rating	Ambient Rating C = 40Â°C
Refrigerant	R290
External Dimensions (mm)	790mm (W) x 840mm (D) x 870mm (H)
Other Details	Reach-In
Power Information	Power supply = 220-240V-1N 50Hz
Power Usage	Power usage kWh/24hr/mÂ² = 38
Door Information	Door hinged = Left
Internal Colour	Stainless Steel
Tray Capacity & Height	8 Trays (GN1/1 or 600x400) (20 mm high) 5 Trays (GN1/1 or 600x400) (40 mm high) 4 Trays (GN1/1 or 600x400) (65 mm high)
Clear Ventilation Space Required	75mm back and sides
HACCP Memory & Alarm	Yes
Data Download Capability	WIFI module included for the HACCP report download
Gastronorm	Yes
About the Product	IRINOX-MF-NEXT-S-TURBO is a propane blast chiller, ecological and completely customizable according to the needs of each professional choosing functions, type of performance, size of the display and the most useful features for its use.
Manufacturer's Suggested Retail Price	\$0.00