



<https://www.commercialfridgefreezer.com.au/thermoline-ti-150g-gravity-convection-premium-incubator/>

Thermoline TI-150G Gravity Convection Premium Incubator 150L



Thermoline TI-150G Gravity Convection Premium Incubator 150L has an internal dimension of 500mm (W) x 520mm (D) x 570mm (H), an external dimension of 570mm (W) x 600mm (D) x 810mm (H), a storage capacity of 150 litres, 3 shelves, and 290 watts of electricity.

Description

Thermoline TI-150G Gravity Convection Premium Incubator 150L

Features include:

- Stainless steel
- Easy to clean
- Corrosion resistant
- Adjustable open wire shelves
- Digital temperature display
- Temperature alarms

<https://www.commercialfridgefreezer.com.au/thermoline-ti-150g-gravity-convection-premium-incubator/>

Commercial Fridge and Freezer Sales Australia. All product images are provided for illustration purposes only. All specifications are subject to manufacturer changes without notice, so please check on the manufacturer's website for current product data.

- 13mm cable/ monitoring port hole with rubber plug
- Insulated external door
- Internal glass viewing door
- Auto overtemperature safety
- Over current protection
- Control error codes
- Open sensor detection
- Gravity convection
- Made in Australia

Additional Information

Brand	Thermoline
Model	TI-150G
Temperature Operating Range C	5Â°C - 60Â°C
External Dimensions (mm)	570mm (W) x 600mm (D) x 810mm (H)
Internal Dimensions (mm)	500mm (W) x 520mm (D) x 570mm (H)
Door Information	Solid door
About the Product	Thermoline TI-150G Gravity Convection Premium Incubator 150L temperature is maintained electronically between ambient 5 degrees to 60 degrees centigrade. Thermoline TI-150G has a safety controller.