

Phone: 1300 733 715

Email: admin@fridgeandfreezer.com.au



https://www.commercialfridgefreezer.com.au/turbo-air-k-series-kr65-3g-n-hc-three-glass-door-top-mount-upright-refrigerator/

Turbo Air K-Series KR65-3G-N(HC) Three Glass Door Top Mount Upright Refrigerator

\$6,360.00 +GST

View more Product Details

Add to Cart

Request a Quote



ntroducing the Turbo Air K-Series KR65-3G-N(HC) Three Glass Door Top Mount Upright Refrigerator, a reliable and efficient refrigeration solution designed for commercial use. This refrigerator features a top-mounted design with three glass doors, providing easy visibility and convenient access to your stored products. Equipped with a digital temperature control system and a high-tech monitor, you can precisely adjust and monitor the inner temperature of the refrigerator. The temperature can be set between 1° and 8°, ensuring optimal storage conditions for your perishable items.

Description

The Turbo Air K-Series KR65-3G-N(HC) Three Glass Door Top Mount Upright Refrigerator is a commercial refrigeration unit designed for efficient cooling and display of food items. It is equipped with advanced features to meet the needs of businesses in the food industry while providing a visually appealing display.

This refrigerator features a digital temperature control system that allows you to easily set and monitor the internal temperature according to your specific requirements. The high-tech monitor provides real-time information about the

operating status and temperature conditions, enabling precise control and monitoring. With its three glass doors and top-mounted configuration, this upright fridge offers convenient access to the stored items while also providing an attractive display for customers. The glass doors allow for easy visibility of the contents, making it ideal for showcasing products in commercial settings.

The self-cleaning condenser feature helps prevent dust accumulation, ensuring optimal performance and reducing the need for maintenance. This results in improved efficiency and durability of the refrigeration system. The refrigerator utilizes the HC refrigerant, which is an environmentally friendly option. It also incorporates a hot gas condensate system, which effectively prevents condensation and ensures efficient operation. With a capacity of 1876 liters, this refrigerator provides ample space for storing a large quantity of food items. The inner temperature can be set within the range of 1° to 8°, allowing for flexible storage options.

Turbo Air - Digital Temperature Control System 3 Glass doors Upright Fridge Top mounted High-Tech Monitor Self Cleaning Condenser Applied HC Refrigerant applied Hot Gas Condensate System Capacity- 1876L Inner Temps 1 to 8 Ventilated Cooling High-Density and CFC free Polyurethane Insulation Adjustable, Heavy Duty, PE Coated Wire Shelves Stainless steel exterior and Interior Refrigerant R-290 Amps 3.0, Power-w 450 Dimensions 1900x850x1926mm Inc Castors Weight 167kg 220V-240v/50Hz/1, 10amp Australian Plug 9 Adjustable shelves included

Additional Information

Country of ManufactureAsiaExternal ColourStainless SteelBrandTurbo AirModelKR65-3G-NWarranty3 Years on Parts and LabourTemperature Operating Range C1°~8°Temperature Display / ControlDigital controlClimate / Ambient Temperature Rating35°RefrigerantR-290External Dimensions (mm)1900 mm (W) x 850 mm (D) x 1926 mm (H)Capacity/Volume1876Other DetailsTurbo Air Self Cleaning Condenser Upright Top Mount on castorsPower Usage280WDoor InformationDoor hinged = LH, RH	External Colour Brand Turbo Air Model KR65-3G-N Warranty 3 Years on Parts and Labour Temperature Operating Range C Temperature Display / Control Climate / Ambient Temperature Rating Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage		
Brand Turbo Air Model KR65-3G-N Warranty 3 Years on Parts and Labour Temperature Operating Range C 1°~8° Temperature Display / Control Digital control Climate / Ambient Temperature Rating 35° Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W	Brand Turbo Air Model KR65-3G-N Warranty 3 Years on Parts and Labour Temperature Operating Range C 1°~8° Temperature Display / Control Digital control Climate / Ambient Temperature Rating 35° Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Country of Manufacture	Asia
Model KR65-3G-N Warranty 3 Years on Parts and Labour Temperature Operating Range C 1°~8° Temperature Display / Control Digital control Climate / Ambient Temperature Rating 35° Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W	Model KR65-3G-N Warranty 3 Years on Parts and Labour Temperature Operating Range C 1°~8° Temperature Display / Control Digital control Climate / Ambient Temperature Rating 35° Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	External Colour	Stainless Steel
Warranty 3 Years on Parts and Labour Temperature Operating Range C 1°~8° Temperature Display / Control Digital control Climate / Ambient Temperature Rating 35° Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W	Warranty Temperature Operating Range C Temperature Display / Control Climate / Ambient Temperature Rating Refrigerant External Dimensions (mm) Capacity/Volume Other Details Power Usage Door Information Packaged Dimensions (mm) 3 Years on Parts and Labour 1°~8° R-28° R-290 External Control Digital control As 5° R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Brand	Turbo Air
Temperature Operating Range C Temperature Display / Control Climate / Ambient Temperature Rating Refrigerant Retrigerant External Dimensions (mm) Capacity/Volume Other Details Power Usage 1°~8° Digital control Regrigerant R-290 R-290 1900 mm (W) x 850 mm (D) x 1926 mm (H) Turbo Air Self Cleaning Condenser Upright Top Mount on castors 280W	Temperature Operating Range C Temperature Display / Control Digital control Climate / Ambient Temperature Rating Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1°~8° R-290 R-290 R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage Door Information Door hinged = LH, RH	Model	KR65-3G-N
Temperature Display / Control Climate / Ambient Temperature Rating Refrigerant External Dimensions (mm) Capacity/Volume Other Details Power Usage Digital control Br-290 R-290 1900 mm (W) x 850 mm (D) x 1926 mm (H) 1876 Turbo Air Self Cleaning Condenser Upright Top Mount on castors 280W	Temperature Display / Control Climate / Ambient Temperature Rating Refrigerant R-290 External Dimensions (mm) Capacity/Volume Other Details Power Usage Door Information Packaged Dimensions (mm) Digital control Door hinged = LH, RH Packaged Dimensions (mm) Digital control Digital control Door hinged = LH, RH Packaged Dimensions (mm) Digital control Door hinged = LH, RH Packaged Dimensions (mm)	Warranty	3 Years on Parts and Labour
Climate / Ambient Temperature Rating 35° Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W	Climate / Ambient Temperature Rating Refrigerant R-290 External Dimensions (mm) Capacity/Volume 1876 Other Details Power Usage Door Information Door hinged = LH, RH Packaged Dimensions (mm) Packaged Dimensions (mm) Packaged Dimensions (mm) R-290 1900 mm (W) x 850 mm (D) x 1926 mm (H) 1876 Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Temperature Operating Range C	1°~8°
Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W	Refrigerant R-290 External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Temperature Display / Control	Digital control
External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W	External Dimensions (mm) 1900 mm (W) x 850 mm (D) x 1926 mm (H) Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Climate / Ambient Temperature Rating	35°
Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W	Capacity/Volume 1876 Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Refrigerant	R-290
Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W	Other Details Turbo Air Self Cleaning Condenser Upright Top Mount on castors Power Usage 280W Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	External Dimensions (mm)	1900 mm (W) x 850 mm (D) x 1926 mm (H)
Power Usage 280W	Power Usage 280W Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Capacity/Volume	1876
	Door Information Door hinged = LH, RH Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Other Details	Turbo Air Self Cleaning Condenser Upright Top Mount on castors
Door Information Door hinged = LH, RH	Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Power Usage	280W
		Door Information	Door hinged = LH, RH
Packaged Dimensions (mm) 1946 mm (W) x 956mm (D) x 2015mm (H)	Interior Lighting Yes	Packaged Dimensions (mm)	1946 mm (W) x 956mm (D) x 2015mm (H)
Interior Lighting Yes		Interior Lighting	Yes

1/9/24

GEMS & MEPS Approved	Yes
Manufacturer's Suggested Retail Price	\$7,950.00