



<https://www.commercialfridgefreezer.com.au/turbo-air-k-series-kur12-2-n-hc-stainless-steel-2-solid-doors-under-bench-refrigerator/>

Turbo Air K-Series KUR12-2-N(HC) Stainless Steel 2 Solid Doors Under Bench Refrigerator

\$2,584.00 +GST

[View more Product Details](#)

[Add to Cart](#)

[Request a Quote](#)



Introducing the Turbo Air K-Series KUR12-2-N(HC) Stainless Steel 2 Solid Doors Under Bench Refrigerator, a reliable and efficient refrigeration solution for commercial kitchens. This underbench fridge features two solid doors, offering convenient access to your chilled products. The left-hand side compressor and front breathing system ensure optimal performance and easy installation. With a high-tech monitor and digital temperature control system, you can easily adjust and monitor the temperature for precise cooling conditions. The refrigerator utilizes HC refrigerant and incorporates a hot gas condensate system for improved efficiency. With a capacity of 311L, it provides ample space for your food storage needs. The inner temperature range of 1 to 8 degrees Celsius allows for optimal food preservation.

Description

Introducing the Turbo Air K-Series KUR12-2-N(HC) Stainless Steel 2 Solid Doors Under Bench Refrigerator, a reliable and efficient solution for your commercial kitchen's refrigeration needs. This underbench fridge features two solid doors, providing ample

<https://www.commercialfridgefreezer.com.au/turbo-air-k-series-kur12-2-n-hc-stainless-steel-2-solid-doors-under-bench-refrigerator/>

Commercial Fridge and Freezer Sales Australia. All product images are provided for illustration purposes only. All specifications are subject to manufacturer changes without notice, so please check on the manufacturer's website for current product data.

storage space and convenient access to your chilled products. Equipped with a digital temperature control system and a high-tech monitor, you can easily set and monitor the internal temperature of the refrigerator, ensuring optimal storage conditions for your perishable items. The left-hand side compressor and front breathing system make installation hassle-free, allowing for flexible placement in your kitchen setup.

This refrigerator utilizes HC refrigerant and a hot gas condensate system, offering energy-efficient cooling while maintaining consistent and reliable performance. With a capacity of 311 liters, you have plenty of space to organize and store your chilled goods. The ventilated cooling system ensures even distribution of cool air throughout the unit, keeping your products fresh. Designed with high-density and CFC-free polyurethane insulation, this refrigerator provides excellent insulation properties to maintain consistent temperatures while promoting energy savings. The stainless steel exterior and interior construction not only offer durability and longevity but also make cleaning and maintenance a breeze.

Operating on a 220V-240V/50Hz/1 power supply with a 10amp plug, this refrigerator is designed for easy installation in most commercial kitchen environments. The unit's dimensions of 1200mm x 700mm x 855mm (including castors) and weight of 84kg make it compact and manageable, maximizing your available space.

Turbo Air - Digital Temperature Control System
2 Solid doors Underbench Fridge
Left hand side Compressor
Front breathing system applied
High-Tech Monitor
HC Refrigerant applied
Hot Gas Condensate System
Capacity - 311L
Inner Temps 1 to 8
Ventilated Cooling
High-Density and CFC free Polyurethane Insulation
Adjustable, Heavy Duty, PE Coated Wire Shelves
Stainless steel exterior and Interior
Refrigerant R-290 Amps 1.4, Power 280W
Dimensions 1200x700x855mm Inc Castors
Weight 84Kgs
220V-240v/50Hz/1, 10amp plug
2 Adjustable shelves included

Additional Information

Country of Manufacture	Asia
External Colour	Stainless Steel
Brand	Turbo Air
Model	KUR12-2-N
Warranty	3 Years on Parts and Labour
Temperature Operating Range C	1°~8°
Temperature Display / Control	Digital control
Climate / Ambient Temperature Rating	35°
Refrigerant	R-290
External Dimensions (mm)	1200 mm (W) x 700 mm (D) x 855 mm (H)
Capacity/Volume	311
Other Details	Turbo Air Self Cleaning Condenser Upright Top Mount on castors
Power Usage	280W

Packaged Dimensions (mm)	1270 mm (W) x 760 mm (D) x 925 mm (H)
GEMS & MEPS Approved	Yes
Manufacturer's Suggested Retail Price	\$3,230.00