



<https://www.commercialfridgefreezer.com.au/turbo-air-k-series-kur12-3d-3-n-hc-stainless-steel-1-solid-door-3-drawer-under-bench-refrigerator/>

# Turbo Air K-Series KUR12-3D-3-N(HC) Stainless Steel 1 Solid Door 3 Drawer Under Bench Refrigerator

**\$3,504.00** +GST

[View more Product Details](#)

[Add to Cart](#)

[Request a Quote](#)



The Turbo Air K-Series KUR12-3D-3-N(HC) Stainless Steel 1 Solid Door 3 Drawer Under Bench Refrigerator is a versatile and efficient refrigeration solution designed for commercial kitchens. This unit features one solid door and three drawers, providing convenient storage options for your perishable items. Equipped with a digital temperature control system and a high-tech monitor, you have precise control over the inner temperature, which can be set between 1 to 8 degrees Celsius. The left-hand side compressor and front breathing system make installation and maintenance hassle-free. The refrigerator utilizes HC refrigerant and incorporates a hot gas condensate system, ensuring optimal performance while being environmentally friendly.

## Description

Introducing the Turbo Air K-Series KUR12-3D-3-N(HC) Stainless Steel 1 Solid Door 3 Drawer Under Bench Refrigerator, a reliable and efficient refrigeration solution for your commercial kitchen. This underbench fridge features one solid door and three

<https://www.commercialfridgefreezer.com.au/turbo-air-k-series-kur12-3d-3-n-hc-stainless-steel-1-solid-door-3-drawer-under-bench-refrigerator/>

Commercial Fridge and Freezer Sales Australia. All product images are provided for illustration purposes only. All specifications are subject to manufacturer changes without notice, so please check on the manufacturer's website for current product data.

drawers, providing versatile storage options for your chilled products. Equipped with a digital temperature control system and a high-tech monitor, you have precise control over the internal temperature of the refrigerator. This ensures that your perishable items are stored at the optimal temperature for freshness and quality. The left-hand side compressor and front breathing system make installation easy and flexible in various kitchen configurations.

Constructed with high-density and CFC-free polyurethane insulation, this refrigerator offers excellent insulation properties, promoting energy efficiency and reducing operational costs. The stainless steel exterior and interior (SUS 439) provide durability, corrosion resistance, and ease of cleaning. Operating on a 220V-240V/50Hz/1 power supply with a 10amp plug, this refrigerator is designed for easy installation in most commercial kitchen settings. With dimensions of 1200mm x 700mm x 855mm (including castors) and a weight of 97kg, it is compact and manageable, maximizing your available space.

The refrigerator includes one adjustable shelf for flexible storage options. Please note that GN pans are not included, and the maximum compatible depth for GN pans is 100mm. Additionally, it does not feature LED lighting.

#### Turbo Air - Digital Temperature Control System

1 Door 3 Drawers Underbench Fridge

Left hand side Compressor

Front breathing system applied

High-Tech Monitor

HC Refrigerant applied

Hot Gas Condensate System

Capacity - 1 door & 3 full size 100mm deep GN-pans (155?????????? + 3 X 1/1 GN pans)

Inner Temps 1 to 8

Ventilated Cooling

High-Density and CFC free Polyurethane Insulation

Stainless steel exterior and Interior SUS 439

Refrigerant R-290 Amps 1.4, Power 280W

Dimensions 1200x700x855mm Inc Castors

Weight 97Kgs

220V-240v/50Hz/1, 10amp plug

1 Adjustable shelves included

GN pans not included

Maximum 100mm deep GN pan

No LED

## Additional Information

|                                      |  |
|--------------------------------------|--|
| Country of Manufacture               | Asia   |
| External Colour                      | Stainless Steel  |
| Brand                                | Turbo Air  |
| Model                                | KUR12-3D-3-N   |
| Warranty                             | 3 Years on Parts and Labour                                    |
| Temperature Operating Range C        | 1°~8°  |
| Temperature Display / Control        | Digital control  |
| Climate / Ambient Temperature Rating | 35°  |
| Refrigerant                          | R-290  |
| External Dimensions (mm)             | 1200 mm (W) x 700 mm (D) x 855 mm (H)                          |
| Capacity/Volume                      | 311  |
| Other Details                        | Turbo Air Self Cleaning Condenser Upright Top Mount on castors |
| Power Usage                          | 280W   |

|                                       |                                       |
|---------------------------------------|---------------------------------------|
| Packaged Dimensions (mm)              | 1270 mm (W) x 760 mm (D) x 925 mm (H) |
| GEMS & MEPS Approved                  | Yes                                   |
| Manufacturer's Suggested Retail Price | \$4,380.00                            |