



<https://www.commercialfridgefreezer.com.au/pinnacle-pr-p-1150-2-gd-medical-refrigerator-p-series-1150/>

Pinnacle PR-P-1150-2-GD - Medical Refrigerator P Series 1150L

\$7,095.00 +GST

[View more Product Details](#)

[Add to Cart](#)

[Request a Quote](#)



Pinnacle PR-P-1150-2-GD - Medical Refrigerator P Series 1150L

Pinnacle Scientific has developed a purpose-built range of fan-forced pharmacy refrigerators. Designed to have both a large storage capacity and refrigeration capacity, this is the premium range of Pinnacle Scientific Pharmacy Refrigerators. The 'P' Series Refrigerators are best suited to universities, hospitals, pharmacies, vet clinics, and clinical trial organizations that have a moderate to high turnover of products.

Description

Pinnacle PR-P-1150-2-GD - Medical Refrigerator P Series 1150L

- High-Efficiency Insulation: Reduces running costs and improves internal conditions,
- LED Lighting: Offers long-life operation and reduces heat load inside the cabinet,
- Cyclic Defrost (Fan Forced): The fan-forced evaporator within the unit improves temperature uniformity and is

<https://www.commercialfridgefreezer.com.au/pinnacle-pr-p-1150-2-gd-medical-refrigerator-p-series-1150/>

Commercial Fridge and Freezer Sales Australia. All product images are provided for illustration purposes only. All specifications are subject to manufacturer changes without notice, so please check on the manufacturer's website for current product data.

automatically defrosted during an off cycle,

- Door Switch: Stops the fan when the door opens and reduces temperature fluctuations,
- Door Lock: To give product security,
- Digital Controller: Digital controller with minimum and maximum temperature logging,
- Cable Port Hole: For remote data loggers and probes,
- Castors: Large castors make moving the refrigerator easier,
- Coated Wire Shelves: Open wire design to improve air circulation around the product,
- Remote Alarm Contacts (BMS): This feature is primarily used by facilities that are not staffed 24hrs a day. The normally closed set of contacts will open if there is a high-temperature, low-temperature alarm, or power failure. Most often these alarm contacts can be hooked into the existing alarm system within the facility making it very cost-effective.

Optional Features:

- Guardian T Alarm Testing Facility with 7-day Chart Recorder: Records the temperature within the refrigerator and continually plots it on a 7-day rotating graph,
- External Temperature Logger: The loggers are a standalone item to the unit controller that continuously logs the temperature within the cabinet,
- Auto Dialler: For alarm notifications via SMS or phone call. Available in 4G and WIFI,
- Additional Shelving For maximum storage utilization,
- Uninterrupted Power Supply (UPS): For continued power supply during black/brownouts.

Additional Information

Brand	Pinnacle
Model	PR-P-1150-1-GD
Warranty	2 Years Parts and Labour
Temperature Operating Range C	5°C Factory Setting (4°C to 6°C)
Temperature Display / Control	Digital with LCD display
Climate / Ambient Temperature Rating	<32°C
Refrigerant	R290
External Dimensions (mm)	1310mm (W) X 825mm (D) X 1965mm (H)
Leg / Caster information	Castors
Door Information	Triple Glazed Glass Insert Solid Door (special order only)
Interior Lighting	Yes
No. of Shelves Included	5 shelves / door
About the Product	Commercial Fridge & Freezer Sales Australia is committed to Providing best price, best quality , best brands and best support in Australia.