

Phone: 1300 733 715

Email: admin@fridgeandfreezer.com.au



https://www.commercialfridgefreezer.com.au/pinnacle-20-static-1-solid-door-p-series-spark-proof-laboratory-upright-freezer-630l/

# Pinnacle -20 Static 1 Solid Door P Series Spark Proof Laboratory Upright Freezer 630L

\$5,471.00 +GST

**View more Product Details** 

**Add to Cart** 

**Request a Quote** 



### Pinnacle -20 Static 1 Solid Door P Series Spark Proof Laboratory Upright Freezer 630L

The Pinnacle purpose-built, spark-proof freezers are an innovative creation, meticulously designed in Australia to ensure the secure storage of volatile samples. These freezers are an ideal choice for laboratories, pharmacies, and hospitals that require a temperature-controlled environment devoid of any ignition sources, thereby ensuring safety and efficiency.

Our range of -20 Spark Proof Freezers is available in various capacities, including 115L, 600L, and 630L. These freezers are specifically designed to meet the needs of different spaces, ensuring you have the most suitable solution for your specific requirements.

# **Description**

#### Pinnacle -20 Static 1 Solid Door P Series Spark Proof Laboratory Upright Freezer 630L

- High-Efficiency Insulation: Reduces running costs and improves internal conditions,
- LED Lighting: Offers long-life operation and reduces heat load inside the cabinet,
- Cyclic Defrost (Fan Forced): The fan-forced evaporator within the unit improves temperature uniformity and is automatically defrosted during an off cycle,
- Door Switch: Stops the fan when the door opens and reduces temperature fluctuations,
- Door Lock: To give product security,
- Digital Controller: Digital controller with minimum and maximum temperature logging,
- Cable Port Hole: For remote data loggers and probes,
- Castors: Large castors make moving the refrigerator easier,
- Coated Wire Shelves: Open wire design to improve air circulation around the product,
- Remote Alarm Contacts (BMS): This feature is primarily used by facilities that are not staffed 24hrs a day. The normally closed set of contacts will open if there is a high-temperature, low-temperature alarm, or power failure. Most often these alarm contacts can be hooked into the existing alarm system within the facility making it very cost-effective.

## **Additional Information**

External Colour	Stainless Steel
Brand	Pinnacle
Model	PSPF-P-20-630-1-SD
Warranty	2 Years Parts and Labour
Temperature Operating Range C	-20°C
Temperature Display / Control	Digital with LCD display
Refrigerant	R290
External Dimensions (mm)	780mm (W) X 825mm (D) X 1965mm (H)
Leg / Caster information	Casters
Power Information	220 VAC - 240 VAC 50Hz
Door Information	Solid Door
Interior Lighting	Yes
Defrost Auto or Manual	Manual
No. of Shelves Included	5 / door
About the Product	Commercial Fridge & Freezer Sales Australia is committed to Providing best price, best quality , best brands and best support in Australia.