



<https://www.commercialfridgefreezer.com.au/skope-prospec-pg11-ubr-2-d6-6-drawer-2-bay-underbench-gn1-1-fridge/>

SKOPE ProSpec PG11.UBR.2.D6 6 Drawer 2 Bay Underbench GN1/1 Fridge

\$6,540.00 +GST

[View more Product Details](#)

[Add to Cart](#)

[Request a Quote](#)



SKOPE ProSpec PG11.UBR.2.D6 6 Drawer 2 Bay Underbench GN1/1 Fridge

A chef's precision is crafted into every detail with the ProSpec. Setting the new benchmark for commercial refrigeration, including a sleek, clean aesthetic, fully configurable, high-spec performance, and integrated food safety data collection. Mold the ProSpec to work for you. Mix and match your desired number of bays, doors, drawers, or both. Available in left or right-hand services.

Description

SKOPE ProSpec PG11.UBR.2.D6 6 Drawer 2 Bay Underbench GN1/1 Fridge

- Dimensions: 1290 W x 700 D x 850 H (mm),
- Material: 304 AISI stainless steel,
- Gross Volume (Litres): 288,
- Total Floor Area (m²): 0.9,
- Refrigeration Unit: Self-Contained,
- Temperature Range: 1 to 4 (adjustable from -2 to 15 with SKOPE-connect),
- Max Ambient Temperature: 40,
- Refrigerant: R290 / 80g (natural refrigerant),
- GEMS Class: 5M1,
- GEMS Energy Consumption (kWh/24h): 2.10,
- GEMS Annual Running Costs: 230,

<https://www.commercialfridgefreezer.com.au/skope-prospec-pg11-ubr-2-d6-6-drawer-2-bay-underbench-gn1-1-fridge/>

Commercial Fridge and Freezer Sales Australia. All product images are provided for illustration purposes only. All specifications are subject to manufacturer changes without notice, so please check on the manufacturer's website for current product data.

- Current Draw (Amps): 2.0,
- Controller: SCS Connect (SKOPE-connect compatible),
- Refrigeration System: Removable cartridge,
- Power Cord: 2 m power cord with 3-pin, 10 amp plug,
- Power Supply: 220-240 volts a.c. 50Hz, single-phase supply.

Options:

- 2 Drawers per Door,
- 3 Drawers per Door,
- Plinth Mounting.

Additional Information

Country of Manufacture	Asia
External Colour	Stainless Steel
Brand	Skope
Model	PG11.UBR.2.D6
Temperature Operating Range C	1°C to 4°C (adjustable* from -2°C to +15°C)
Climate / Ambient Temperature Rating	Ambient Rating C = 40°C
GEMS Product Temperature Class	5M1 (-1°C to 5°C)
GEMS energy consumption	2.10kWh/24h
GEMS annual running cost	\$230 (@ \$0.30/kWh)
Temperature Display / Control	SCS Connect (SKOPE-connect™ compatible)
Refrigerant	R290 / 80g
External Dimensions (mm)	1290mm (W) x 700mm (D) x 850mm (H) (Standard castors) / 860 - 900 mm (Legs) / 715 mm (Plinth mount)
Internal Dimensions (mm)	820mm (W) x 580mm (D) x 605mm (H)
Capacity/Volume	288ltr
Leg / Caster information	Standard castors / Legs / Plinth mount
Power Information	220-240 volts a.c., 50 Hz, single-phase supply
Door Information	Drawer: 300mm (W) X 525mm (D) X 100mm (H)
Packaged Dimensions (mm)	TBC
Internal Colour	Stainless Steel
Defrost Auto or Manual	Automatic
Clear Door Opening Width	1305mm
Clear Ventilation Space Required	Not required
Gastronorm	Yes
About the Product	Commercial Fridge & Freezer Sales Australia is committed to providing best price, best quality brands and best support in Australia.
Manufacturer's Suggested Retail Price	\$8,175.00