

Phone: 1300 733 715

Email: admin@fridgeandfreezer.com.au



https://www.commercialfridgefreezer.com.au/fresh-refrigeration-ft-900r-one-door-900mm-wide-underbench-fridge-186l/

Fresh Refrigeration FT-900R One Door 900mm Wide 186L Underbench Fridge

\$2,371.73 +GST

View more Product Details

Add to Cart

Request a Quote



Fresh Refrigeration FT-900R One Door 900mm Wide Underbench Fridge, a top-of-the-line refrigeration solution that combines cutting-edge technology with robust construction. This fridge boasts a digital temperature control and monitoring system, ensuring precise temperature management, while the hot gas condensate system and automatic evaporation and defrost system keep it operating efficiently. Its stainless steel finish on the top, front, sides, and doors not only adds a touch of modern elegance but also enhances durability. The inclusion of heavy-duty casters with brakes and PE coated sturdy wire shelves make this fridge both functional and convenient. With a temperature range of 32°F41°F (0°C5°C), it's ideal for preserving your products in optimal conditions. The Fresh Refrigeration FT-900R is a reliable and stylish choice for any commercial kitchen or food establishment.

Description

Fresh Refrigeration FT-900R One Door 900mm Wide Underbench Fridge, 186L

, a premium refrigeration solution designed to meet your cooling needs with precision and durability. This cutting-edge appliance boasts a sophisticated digital temperature control and monitoring system, ensuring that your stored items are maintained at the perfect temperature range of 32°F41°F (0°C5°C). With an automatic evaporation and defrost system, you can bid farewell to manual maintenance hassles.

Crafted for longevity, the FT-900R features a robust stainless steel finish on its top, front, sides, and doors, while the galvanized steel finish on the back and bottom adds extra protection. Its modern one-piece grill not only enhances aesthetics but also contributes to its overall resilience. Inside, you'll find PE-coated sturdy wire shelves for convenient storage. Moving this fridge is a breeze thanks to the 4" heavy-duty casters with brakes, ensuring both mobility and stability. The Fresh Refrigeration FT-900R is your reliable partner for all your refrigeration needs, combining functionality, durability, and style in one sleek package.

- · Precise digital temperature control and monitoring
- Efficient hot gas condensate system
- Automatic evaporation and defrost system for convenience
- Top, front, sides, and doors finished in durable stainless steel
- Back and bottom made from galvanized steel for longevity
- Sleek and contemporary one-piece grill design
- Sturdy wire shelves coated with PE for durability

Additional Information

Country of ManufactureKoreaExternal ColourStainless SteelBrandFresh RefrigerationModelFT-900RWarranty2 Year Parts and LabourTemperature Operating Range C0°C ~ 5°CGEMS & MEPS ApprovedYesTemperature Display / ControlDigital controlRefrigerantR-134aExternal Dimensions (mm)900 mm (W) x 700 mm (D) x 846 mm (H)Capacity/VolumeVolume: 186 LitersOther DetailsVoltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66Power InformationPower Supply = 2 AmpsPower Usage340 W
Brand Fresh Refrigeration Model FT-900R Warranty 2 Year Parts and Labour Temperature Operating Range C 0°C ~ 5°C GEMS & MEPS Approved Yes Temperature Display / Control Digital control Refrigerant R-134a External Dimensions (mm) 900 mm (W) x 700 mm (D) x 846 mm (H) Capacity/Volume Volume: 186 Liters Other Details Voltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66 Power Information Power Supply = 2 Amps Power Usage 340 W
Model FT-900R Warranty 2 Year Parts and Labour Temperature Operating Range C 0°C ~ 5°C GEMS & MEPS Approved Yes Temperature Display / Control Digital control Refrigerant R-134a External Dimensions (mm) 900 mm (W) x 700 mm (D) x 846 mm (H) Capacity/Volume Volume: 186 Liters Other Details Voltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66 Power Information Power Supply = 2 Amps Power Usage 340 W
Warranty Z Year Parts and Labour Temperature Operating Range C GEMS & MEPS Approved Yes Temperature Display / Control Refrigerant R-134a External Dimensions (mm) Capacity/Volume Other Details Power Information Power Usage Z Year Parts and Labour O°C ~ 5°C Digital control Refrigerant R-134a External Dimensions (mm) Yolume: 186 Liters Voltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66 Power Usage 340 W
Temperature Operating Range C GEMS & MEPS Approved Yes Temperature Display / Control Refrigerant Refrigerant External Dimensions (mm) Capacity/Volume Other Details Power Information Power Usage O°C ~ 5°C Yes Yes Ness Yes Ness Volume Ness Power Usage O°C ~ 5°C Yes Ness Yes Ness Ness Ness Volume Ness N
GEMS & MEPS Approved Temperature Display / Control Refrigerant R-134a External Dimensions (mm) Capacity/Volume Other Details Power Information Power Usage Yes Yes Yes Yes Yes Digital control R-134a R-134a External Dimensions (mm) 900 mm (W) x 700 mm (D) x 846 mm (H) Volume: 186 Liters Volume: 186 Liters Power Supply = 2 Amps 340 W
Temperature Display / Control Refrigerant R-134a External Dimensions (mm) Capacity/Volume Other Details Power Information Power Usage Digital control R-134a R-134a Yolume: 186 Liters Volume: 186 Liters Voltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66 Power Supply = 2 Amps 340 W
Refrigerant R-134a External Dimensions (mm) 900 mm (W) x 700 mm (D) x 846 mm (H) Capacity/Volume Volume: 186 Liters Other Details Voltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66 Power Information Power Supply = 2 Amps Power Usage 340 W
External Dimensions (mm) 900 mm (W) x 700 mm (D) x 846 mm (H) Capacity/Volume Volume: 186 Liters Other Details Voltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66 Power Information Power Supply = 2 Amps Power Usage 340 W
Capacity/Volume Other Details Voltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66 Power Information Power Supply = 2 Amps 340 W
Other Details Voltage_(V/Hz/Ř): 220/50,60/1 HP: 1/3 Gross Weight: 66 Power Information Power Supply = 2 Amps 340 W
Power Information Power Supply = 2 Amps Power Usage 340 W
Power Usage 340 W
Interior Lighting Yes
Defrost Auto or Manual Automatic
About the Product Discover the best price for the Fresh Refrigeration FT-900R, a single-door, 900mm wide Underbench Fridge. Purchase the FT-900R and all other commercial Underbench Fridges with Australia-wide delivery options.
Notes For WA customers there will be an extra surcharge of \$880.00 + GST per cabinet for delivery over and above the standard freight cost over the online freight matrix your invoice will be adjusted by our team.
Product Options - Drawer mixed model available - Free HCFC & HFC refrigerant model (R-290)